



# 1Y0-241<sup>Q&As</sup>

Deploy and Manage Citrix ADC with Traffic Management

## Pass Citrix 1Y0-241 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/1y0-241.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Citrix  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

Scenario: A Citrix Administrator executed the following commands on the Citrix ADC: > add policy dataset Admin\_group ipv4 > bind policy dataset Admin\_group 192.168.149.10 -index 11 > bind policy dataset Admin\_group 192.168.149.39 -index 12 > bind policy Admin\_group 192.168.149.49 -index 13 > add responder policy POL\_1 "!(CLIENT.IP.SRC.TYPECAST\_TEXT\_T.CONTAINS\_ANY(\"Admin\_group\"))" RESET > bind lb vServer lb\_vsrv\_www -policyName POL\_1 -priority 100 -gotoPriorityExpression END -type REQUEST What will be the effect of these commands?

- A. Only users with a source IP address of 192.168.149.10, 192.168.149.39, or 192.168.149.49 will be allowed to connect to vServer lb\_vsrv\_www.
- B. Only users with a source IP address of 192.168.149.10, 192.168.149.39, or 192.168.149.49 will be blocked when attempting to connect to vServer lb\_vsrv\_www.
- C. Only users with a source IP address of 192.168.149.10 or 192.168.149.39 will be allowed to connect to vServer lb\_vsrv\_www.
- D. All traffic from users with a source IP address of 192.168.149.10, 192.168.149.39, or 192.168.149.49 will be blocked through the Citrix ADC.

Correct Answer: A

---

**QUESTION 2**

Scenario: Client connections to certain vServers are abnormally high. A Citrix Administrator needs to be alerted whenever the connections pass a certain threshold.

How can the administrator use Citrix Application Delivery Management (ADM) to accomplish this?

- A. Configure network reporting on the Citrix ADM by setting the threshold and email address.
- B. Configure SMTP reporting on the Citrix ADM by adding the threshold and email address.
- C. Configure TCP Insight on the Citrix ADM.
- D. Configure specific alerts for vServers using Citrix ADM.

Correct Answer: A

<https://docs.citrix.com/en-us/citrix-application-delivery-management-service/networks/network-reporting.html>

---

**QUESTION 3**

Which mode on a Citrix ADC can a Citrix Administrator utilize to avoid asymmetrical packet flows and multiple route/ARP lookups?

- A. MAC-based forwarding (MBF)



- B. Use Subnet IP (USNIP)
- C. Layer 3
- D. Layer 2

Correct Answer: C

---

#### QUESTION 4

If VLAN 20 is bound to the interface as tagged in an environment where Citrix ADC is configured with the default settings, which VLANs will be bound to an interface?

- A. VLAN 1 tagged and VLAN 20 tagged
- B. VLAN 20 tagged only
- C. VLAN 1 untagged and VLAN 20 tagged
- D. VLAN 20 untagged only

Correct Answer: C

---

#### QUESTION 5

When a Citrix ADC high availability (HA) pair failover occurs, by what method does the Citrix ADC communicate to the network switches and routers that IP-to-MAC address bindings have changed?

- A. Reverse ARP (RARP) to update the network devices
- B. MAC-based forwarding (MBF) to update the routers
- C. Proxy ARP to update the network devices
- D. Gratuitous ARPs (GARPs) to update the network devices

Correct Answer: D

Reference: <https://www.citrix.com/blogs/2015/01/05/netscaler-best-practice-with-vmac-in-a-high-availabilityconfiguration/>

[Latest 1Y0-241 Dumps](#)

[1Y0-241 PDF Dumps](#)

[1Y0-241 Study Guide](#)