



1Z0-149^{Q&As}

Oracle Database 19c: Program with PL/SQL

Pass Oracle 1Z0-149 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/1z0-149.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Oracle
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

In one of your databases, table HR.EMPLOYEES includes the columns FIRST_NAME and EMPLOYEE_ID.

A row exists with EMPLOYEE_ID 201.

Examine these packages created by user HR:

```
CREATE PACKAGE helper AUTHID DEFINER ACCESSIBLE BY (api) IS
    PROCEDURE h1;
END;
/

CREATE PACKAGE BODY helper IS
    PROCEDURE h1 IS
        emp_name employees.first_name%TYPE;
    BEGIN
        SELECT first_name INTO emp_name FROM hr.employees WHERE employee_id=201;
        DBMS_OUTPUT.PUT_LINE(emp_name);
    END;
END;
/

CREATE PACKAGE api AUTHID CURRENT_USER IS
    PROCEDURE p1;
END;
/

CREATE PACKAGE BODY api IS
    PROCEDURE p1 IS
    BEGIN
        helper.h1;
    END;
END;
/
```

EXECUTE privilege is granted to user SH, on the HR.API and HR.HELPER packages.

Which two will execute successfully? (Choose two.)

- A. Call HR.HELPER.H1 from the HR schema.
- B. Call HR.HELPER.H1 from the SH schema.
- C. Call HR.API.P1 from the HR schema.
- D. Call HR.API.P1 from the SH schema.
- E. Create and call a package procedure API.H1 in the SH schema, which calls HR.HELPER.H1.



Correct Answer: BD

QUESTION 2

Examine this DECLARE section:

```
1 DECLARE
2 v_join_date DATE := SYSDATE - 10;
3 v_flag BOOLEAN NOT NULL DEFAULT TRUE;
4 v_char VARCHAR2 := NULL;
5 v_bonus_pct CONSTANT REAL(2) := 8.25;
6 v_zip_code VARCHAR2(80) := SUBSTR('Oracle Corporation', 24, 0);
```

Which line will cause an error upon execution?

- A. line 5
- B. line 3
- C. line 2
- D. line 4
- E. line 6

Correct Answer: E

QUESTION 3

Which two are valid MODIFIER values for the PLSQL_WARNINGS parameter? (Choose two.)

- A. DISABLE
- B. ENABLE
- C. ERROR
- D. ALL
- E. SEVERE

Correct Answer: DE

QUESTION 4

For which three SYSTEM EVENTS can triggers be created? (Choose three.)



- A. DDL
- B. AFTER AUDIT
- C. BEFORE ANALYZE
- D. SHUTDOWN
- E. SERVERERROR
- F. STARTUP
- G. BEFORE GRANT

Correct Answer: DEF

QUESTION 5

Which code will successfully create a BODILESS PACKAGE to standardize CONSTANTS and EXCEPTIONS declarations?



- A.
- ```
CREATE OR REPLACE PACKAGE std_const_err_pkg IS
vtax CONSTANT NUMBER(3):=3;
e_seq EXCEPTION;
PRAGMA EXCEPTION_INIT(-2277,e_seq);
e_fk EXCEPTION;
PRAGMA EXCEPTION_INIT(-2292,e_fk);
End;
```
- B.
- ```
CREATE OR REPLACE PACKAGE std_const_err_pkg IS
vtax CONSTANT NUMBER(3);
e_seq Exception;
PRAGMA EXCEPTION_INIT(e_seq,-2277);
e_fk EXCEPTION;
PRAGMA EXCEPTION_INIT(e_fk, -2292);
End;
```
- C.
- ```
CREATE OR REPLACE PACKAGE std_const_err_pkg IS
vtax CONSTANT NUMBER(3):=3;
e_seq Exception;
PRAGMA EXCEPTION_INIT(e_seq,-2277);
e_fk EXCEPTION;
PRAGMA EXCEPTION_INIT(e_fk, -2292);
End;
```
- D.
- ```
CREATE OR REPLACE PACKAGE std_const_err_pkg IS
vtax NUMBER(3) CONSTANT:=3;
e_seq Exception;
PRAGMA EXCEPTION_INIT(e_seq,-2277);
e_fk EXCEPTION;
PRAGMA EXCEPTION_INIT(e_fk, -2292);
End;
```



A. Option A

B. Option B

C. Option C

D. Option D

Correct Answer: C

[Latest 1Z0-149 Dumps](#)

[1Z0-149 PDF Dumps](#)

[1Z0-149 Braindumps](#)