



500-230^{Q&As}

Cisco Service Provider Routing Field Engineer

Pass Cisco 500-230 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/500-230.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

What does "ifmgr" represent in the output below?

LC/0/3/CPU0:Mar 23 08:04:31.644 : ifmgr[151]: %PKT_INFRA-LINEPROTO-5-UPDOWN : Line protocol on Interface POS0/3/0/7, changed state to Down

- A. The SYSMGR process restarted the ifmgr process as a result of this log message.
- B. The WDSYMON process is tracking this process to prevent it from bringing the interface up.
- C. The ifmgr process has restarted 151 times and brought the interface down as a result.
- D. The ifmgr process created this log message.

Correct Answer: D

QUESTION 2

Which command is run to make changes permanent and survive a reload after executing the command "copy disk0:config-file.txt running-config"?

- A. Commit Confirm
- B. Commit Copy
- C. Command not require, changes are committed automatically
- D. Commit

Correct Answer: D

QUESTION 3

Which VRFs must be configured on the ASBRs between the two ASes in an Option B Layer-3 VPN solution?

- A. The VRFs shared between the two ASes plus one VRF representing each AS.
- B. The VRFs shared between the two ASes.
- C. The VRFs shared between the two ASes plus one shared VRF.
- D. The VRFs do not need to be configured on the ASBRs.

Correct Answer: B

QUESTION 4

Which statements are true regarding L3VPN configurations?



- A. Prior to configuring a vrf within MP-BGP, the router has to have instantiated the VPNv4 or VPNv6 address-family.
- B. On a single PE router, the Route Distinguisher and the Route Targets must be the same.
- C. Prior to configuring a neighbor in the VPNv4 address-family, it must already be configured for IPv4Unicast.
- D. The import and export Route Targets must be the same on a PE.

Correct Answer: C

QUESTION 5

What is the TRACE command?

- A. A packet tracer showing the path of a packet from ingress to egress in the router.
- B. The replacement for TraceRoute in IOS-XR.
- C. A form of always-on debugging available for a subset of commands.
- D. Exactly the same as the debug command, must be explicitly turned on.

Correct Answer: A

[Latest 500-230 Dumps](#)

[500-230 VCE Dumps](#)

[500-230 Study Guide](#)