



# E20-393<sup>Q&As</sup>

Unity Solutions Specialist Exam for Implementation Engineers

**Pass EMC E20-393 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/e20-393.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by EMC  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

In Unisphere, a storage administrator has inadvertently disabled Data Reduction on an existing LUN. What would result from this action?

- A. A background LUN migration occurs, moving the data to a new LUN where it is inflated. New data is neither deduplicated nor compressed.
- B. Existing data is left in its current state. New data is neither deduplicated nor compressed.
- C. Existing data is dynamically inflated to its full size, undoing the impact of deduplication and compression. New data is neither deduplicated nor compressed.
- D. Data Reduction, once enabled, cannot be disabled. New data is deduplicated or compressed.

Correct Answer: B

---

**QUESTION 2**

How long will a Copy Back operation take when a hot spare is invoked?

- A. Pro-Active hot spare does not use a Copy Back operation
- B. Copy Back time depends on the RAID type
- C. Copy Back time depends on the disk capacity
- D. Copy Back time depends on the disk type

Correct Answer: B

Note: Starting with Release 24, you can now use a proactive hot spare for proactive disk replacement. Before Release 24 you had to remove the physical disk to replace in order to force a rebuild. During the rebuild phase, the RAID group was "degraded" and at risk.

Resolution:

Three main benefits of using a proactive hot spare:

Avoiding "uncorrectable errors" due to media problems during the rebuild process.

Greatly reduce the risk of having a degraded RAID group, and the risk of having a double-faulted RAID group.

Performance - a copy to hot spare is faster than a normal rebuild.

References: <https://community.emc.com/docs/DOC-9419>

---

**QUESTION 3**

Fibre Channel access from a server to the Storage Processor can use what pathing options?



- A. Single Path, Multipath, and Alternate path
- B. Single path and Multipath only
- C. Single Path and Alternate path only
- D. Multipath only

Correct Answer: B

Reference: <https://www.emc.com/collateral/TechnicalDocument/docu69325.pdf>

---

#### QUESTION 4

A company has a VMware host installed with FC HBAs that is connected to a Dell EMC Unity XT storage array. A 500 GB LUN is provisioned to this host from the Unity array and is in production. The VMware administrator has configured a new vSwitch with the NICs on the server intended for iSCSI traffic. The storage administrator is asked to configure software iSCSI and provision a new 1 TB LUN from the storage array via iSCSI.

What is a consideration when satisfying this request?

- A. A connection must be established between the host iSCSI initiators and Unity iSCSI targets before provisioning the new LUN
- B. Any single host should connect to any single array using one protocol only
- C. The iSCSI configuration must use all the NIC connections to the host
- D. Two iSCSI target interfaces must be configured with IP addresses from separate subnets

Correct Answer: D

---

#### QUESTION 5

Which IP connection characteristic is used only for file-based storage configurations on Dell EMC Unity XT?

- A. Link aggregation
- B. VLAN tagging
- C. Bandwidth throttle
- D. Network latency

Correct Answer: B

[E20-393 VCE Dumps](#)

[E20-393 Practice Test](#)

[E20-393 Study Guide](#)