

# JN0-349<sup>Q&As</sup>

Enterprise Routing and Switching - Specialist (JNCIS-ENT)

# Pass Juniper JN0-349 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass4itsure.com/jn0-349.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Juniper Official Exam Center

Instant Download After Purchase

100% Money Back Guarantee

- 😳 365 Days Free Update
- 800,000+ Satisfied Customers





# **QUESTION 1**

You are running a Virtual Chassis with nonstop routing enabled. You want to confirm that the BGP routing table synchronization has completed on the backup Routing Engine.

Which command will show you this information?

- A. show task replication
- B. show bgp summary
- C. show bgp neighbor
- D. show bgp replication
- Correct Answer: D

#### **QUESTION 2**

Click the Exhibit button.

{master:0}	
user@switch> show spanning-tree bridge	ð
STP bridge parameters	
Context ID	: 0
Enabled protocol	: RSTP
Root ID	: 8192.50:c5:8d:ae:db:41
Root cost	: 40000
Root port	: ge-0/0/14.0
Hello time	: 2 seconds
Maximum age	: 40 seconds
Forward delay	: 30 seconds
Message age	: 4
Number of topology changes	: 1
Time since last topology changes	: 64 seconds
Topology change initiator	: ge-0/0/14.0
Topology change last recvd. from	: 2c:6b:f5:31:06:0e
Local parameters	
Bridge ID	: 32768.50:c5:8d:ae:bd:41
Extended system ID	: 0
Internal instance ID	: 0

Referring to the exhibit, which statement is correct?

A. The device is the root bridge?



- B. The spanning tree session has timed out.
- C. The local bridge priority is set to 8k.
- D. The bridge priority on the root device is set to 8k.

Correct Answer: D

# **QUESTION 3**

Which two statements about RSTP are correct? (Choose two.)

- A. RSTP is backward compatible with STP.
- B. RSTP permits multiple root bridges within a Layer 2 domain.
- C. RSTP permits only a single root bridge within a Layer 2 domain.
- D. RSTP is not backward compatible with STP.

Correct Answer: AC

# **QUESTION 4**

Which two statements about a unified ISSU are correct? (Choose two.)

- A. It requires that Bidirectional Forwarding Detection be disabled.
- B. It requires that graceful Routing Engine switchover be enabled.
- C. It is only supported on platforms with redundant control planes.
- D. It is only supported on platforms with redundant power supplies.

Correct Answer: BC

# **QUESTION 5**

You have an OSPF NSSA area that is also receiving IS-IS routes on the ASBR.

In this scenario, which LSA type is used to announce external IS-IS routes?

- A. Type 7
- B. Type 8
- C. Type 1
- D. Type 4
- Correct Answer: A



JN0-349 PDF Dumps

JN0-349 VCE Dumps

JN0-349 Braindumps