

Exam : **HP0-704**

Title : TruCluster v5
Implementation and Support

Version : Demo

www.Pass4itSure.com

1. Which TruCluster daemon must be running on each cluster member for the cluster alias to work?

- A. clu_aliasd
- B. gated
- C. routed
- D. aliasd

Answer: D

2. Which command is used to manage cluster aliases?

- A. clu_create
- B. clu_alias
- C. cfsmgr
- D. cluamgr

Answer: D

3. Which command shuts down all cluster members?

- A. shutdown now
- B. shutdown -r
- C. shutdown -h
- D. shutdown -c

Answer: D

4. What are the four types of CAA resource profiles?

- A. application, tape, changer, and network
- B. application, tape, distributed, and network
- C. application, disk, changer, and network
- D. application, required, changer, and network

Answer:A

5. Which file is used by the cluster alias to determine service attributes?

- A. /etc/ports

B. /etc/alias

C. /etc/clua_services

D. /etc/services

Answer: C

6. Which utility is used within a CAA action script to make events available to the cluster?

A. echo

B. evmwrite

C. DECEvent

D. evmpost

Answer: D

7. What defines member eligibility during a CAA application relocation?

A. application's CAA profile

B. /var/cluster/caa/cluster_config

C. /var/cluster/{members}caa/cluster_config

D. number of CAA applications currently running on the member

Answer:A

8. Which command is used to adjust quorum disk votes?

A. cfsmgr

B. adj_quorum

C. hwmgr

D. clu_quorum

Answer: D

9. Which command is used to gather information about cluster members?

A. clu_get_info

B. cluamgr

C. cnxshow

D. cfsmgr

Answer:A

10. What should be done to isolate Memory Channel errors in a cluster, when all members report the errors?

A. replace one Memory Channel at a time until the errors stop

B. run the Memory Channel diagnostics, mc_cable and mc_diag

C. replace all Memory Channel hardware

D. no corrective action is required

Answer: B

11. What type of application is managed by the CAA software?

A. single-instance

B. multi-instance

C. distributed

D. parallel

Answer:A

12. What is the result of votes falling below quorum value in a TruCluster?

A. members continue to run

B. process activity is suspended on all cluster members

C. all cluster members panic

D. quorum value is automatically lowered

Answer: B

13. Click the Exhibit button to display output from the clu_get_info command. What is the Cluster Interconnect IP name for memberid 2?

A. naclus1-mc0

B. naclus2-mc0

C. naclus3-mc0

D. naclus-mc0

Answer: B

14. What hardware is required to migrate a cluster to a TruCluster Server environment? Select TWO.

A. at least one cluster interconnect device

B. at least two member systems

C. a sharable high volume backup medium

D. sharable storage components - controllers and devices

E. at least one quorum disk

Answer:AD

15. Which TruCluster application scripts must be saved to external files before migrating the application to TruCluster Server?

A. disk mounting

B. network alias

C. start and stop action

D. crashdc data collection

Answer: C

16. Which release of TruCluster software supports TruCluster Server rolling upgrades?

A. 1.5

B. 1.6

C. 5.0

D. 5.0A

Answer: D

17. Which TruCluster application programming interface may be present in a distributed application?

A. DRD

B. asemgr

C. Production Server

D. Memory Channel

Answer: D

18. Which technique is the easiest to manage, when changing hard-coded device names in data files, during the move of distributed applications to TruCluster Server?

- A. rename the data files
- B. create symbolic links
- C. recreate the application database
- D. create DRD services

Answer: B

19. Which techniques allow you to change hard coded device names in data files, while moving distributed applications to TruCluster Server? Select TWO

- A. filter using MC API
- B. clone the data files
- C. create symbolic links
- D. convert to ASE format
- E. recreate the application database

Answer: CE

20. Which requirements must be met when upgrading a cluster from ASE to TruCluster Server? Select TWO.

- A. ASE systems must migrate all UFS file systems to AdvFS file systems
- B. TCR-UA license must be installed and activated on each system
- C. ASE systems must have a supported cluster interconnect adapter or open PCI slots for installing a supported cluster interconnect adapter
- D. ASE system network adapters must be valid for NetRain configurations
- E. storage devices must be converted to dual-redundant configurations

Answer: AC

Trying our product !

- ★ **100%** Guaranteed Success
- ★ **100%** Money Back Guarantee
- ★ **365 Days** Free Update
- ★ **Instant Download** After Purchase
- ★ **24x7** Customer Support
- ★ Average **99.9%** Success Rate
- ★ More than **69,000** Satisfied Customers Worldwide
- ★ Multi-Platform capabilities - **Windows, Mac, Android, iPhone, iPod, iPad, Kindle**

Need Help

Please provide as much detail as possible so we can best assist you.

To update a previously submitted ticket:



Submit A Ticket

One Year Free Update



Free update is available within One Year after your purchase. After One Year, you will get 50% discounts for updating. And we are proud to boast a 24/7 efficient Customer Support system via Email.



Money Back Guarantee

To ensure that you are spending on quality products, we provide 100% money back guarantee for 30 days from the date of purchase.



Security & Privacy

We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.

Guarantee & Policy | Privacy & Policy | Terms & Conditions

Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © 2004-2014, All Rights Reserved.